



Sure-Seal[®] In-Seam Sealant

DESCRIPTION

Sure Seal In-Seam Sealant is a one-part, gun-grade material designed for use in conjunction with PRE-KLEENED EPDM Thru-Wall Flashing. It is primarily used as an internal waterproof seal for cured-to-cured membrane splices.

Sure Seal In-Seam Sealant is an extremely durable material which dries to the touch in about 30 minutes. When cured it has a rubber like consistency and is resistant to all types of weather extremes.

Sure Seal In-Seam Sealant must be applied in each cured-to-cured membrane splice during the splice procedure.

CAUTIONS AND WARNINGS

REVIEW THE APPLICABLE MATERIAL SAFETY DATA SHEET FOR COMPLETE SAFETY INFORMATION PRIOR TO USE.

This product is **FLAMMABLE**. Keep away from sparks and open flame. Do not smoke while using. Keep containers closed when not in use. In case of fire, use water spray, foam, dry chemical or carbon dioxide. Do not use a solid stream of water because it can scatter and spread the fire. Vapors are heavier than air and may travel along ground to distant ignition sources and flash back. Harmful if swallowed or inhaled. Avoid breathing vapors. Wash hands thoroughly after handling. If swallowed, **DO NOT INDUCE VOMITING**. Call physician immediately. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Causes eye irritation. Avoid contact with eyes. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. May cause skin irritation. Avoid contact with skin. Carlisle's special solvent resistant Hycron[®] gloves are recommended. In case of skin contact, thoroughly wash affected area with soap and water. Job site storage temperatures in excess of 90° F (32° C) may affect product shelf life. Should the Sure Seal In-Seam Sealant be stored at temperatures below 60° F (15° C), restore to room temperature prior to use.

COVERAGE

15 lineal feet (4.5 meters) per tube applied as a 3/8" (1 cm) diameter bead. (Coverage rates are average and may vary due to conditions on the job site.)

TECHNICAL DATA

PROPERTY	RESULT
Color	Natural
Solids	75-80%
Specific Gravity	1.13
Brookfield Viscosity	500K to 1M cps
Flashpoint	40°F (closed cup method)
Resistance to Staining, Slump, Water, Acid and Alkali	Excellent
Packaging	10/carton
Shelf Life	12 months (unopened)

APPLICATION

Prepare sheeting for splicing by cleaning the splice with the appropriate cleaner, if necessary. Apply Sure Seal In-Seam Sealant in two beads separated by 2" located 1" from the edge of the splice. Cut the nozzle. Open the foil widely and keep the sealant warm to improve flow. Hot boxes are strongly recommended. Use a low power setting on automatic caulking guns.

LIMITED WARRANTY

Carlisle Coatings and Waterproofing Incorporated (Carlisle) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any Carlisle materials prove to contain manufacturing defects that substantially affect their performance, Carlisle will, at its option, replace the material or refund the purchase price.

This limited warranty is the only warranty extended by Carlisle with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. Carlisle specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of Carlisle's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the Carlisle material in question.

