



CCW-702LV

For Use With Sheet Membranes

DESCRIPTION

CCW-702LV is a quick drying, solvent based, high-tack adhesive specifically designed to promote maximum adhesion of CCW self-adhering membranes.

Apply by medium nap roller (3/8" nap for best results) or brush in an even film at 300 to 350 square feet per gallon. Allow adhesive to dry for 20 minutes minimum at 75° F. Porous substrates will result in reduced coverage rates for proper adhesion. Adhesive has a satisfactory cure when surface is tacky, but will not transfer when touched. Apply only on areas to be waterproofed the same day. Reapply if area becomes dirty or wet. When used in adverse climactic conditions (i.e. humid, cool, etc.) or on a porous substrate, additional time will be required.

PACKAGING

5 Gallon pails, 45 pails per pallet, P/N 316148

Store at 35° to 110°F (2° to 43°C)

CAUTION: Flammable liquid and vapors. Use only with adequate ventilation and avoid breathing vapors. Refer to MSDS for other important warnings and product safety information.

TECHNICAL DATA

PROPERTY	RESULTS
Weight per Gallon	7.5 lbs
Solids Content	46% by wt
VOC Content	less than 250 g/l
Color	Plum Red
Flash Point	-4°F (-20°C)
Adhesion to Concrete	11.0 lb/in
Minimum Application Temp	25°F (3.9°C)
Viscosity	200 cps
Storage Temp	35°F to 110°F

LIMITED WARRANTY

Carlisle Coatings & Waterproofing, Incorporated (Carlisle) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any Carlisle materials prove to contain manufacturing defects that substantially effect their performance, Carlisle will, at its option, replace the materials or refund its purchase price.

This limited warranty is the only warranty extended by Carlisle with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. Carlisle specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of Carlisle's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the Carlisle material in question.

