

INSTALLER CHECK LIST – CCW-5123 VEHICULAR DECK COATING

- CCW Representative Contact Information.**
- Installer Qualification Letter/ Verify Training**
- Verify if components of system match requirements for specified project warranty**
- Pre-Construction Meeting**
- Weather requirements – No frost, moisture present or pending and above 40 degrees**
- Substrate Inspection – See Substrate Inspection Form, ICRI CSP 2-4, 28 day cure (Note: surface prep in critical for success with deck coatings)**
- Follow CCW Plywood Deck Technical Release for plywood substrates**
- Conduct ASTM Rubber Mat Test for moisture**
- Install field mock-up and get owner to sign off on appearance**
- Saw cut and seal cracks over 1/16th inch. Detail and pre-treat all cracks with CCW-501T**
- If metal pan is used, must be vented**
- Always allow for and verify proper cure time between coats**
- CCW Product Data Sheets, MSDSs and Shop Drawings**
- Provide adequate ventilation**
- CCW Inspection Forms**
- Have Access to Project Spec and Drawings**
- CCW Products: 557 Primer, CCW-501-T Detail Coat, CCW-501 Base Coat, CCW-502 Intermediate Coat, 503 Top Coat, CCW-201 Sealant**
- Tools & Supplies:**
 - Solvent Resistant ¾ inch nap roller**
 - Notched Squeegee (1/4 inch notch)**
 - Mil Thickness gauge**
 - Shot blast equipment**
 - Solvent for cleaning**
 - Push broom or vacuum**
 - Appropriate size clean dry rounded silica sand**
 - Duck tape**
 - Angle grinder with concrete blade**
 - Caulk gun**
 - Chalk line**
- Safety Equipment**
 - Personal Protection Devices and OSHA Approved Safety Equipment for all workers on the jobsite**
 - Fire extinguisher**
 - Protective clothing**
 - Respirator**
 - Hard hat**

