

## INSTALLER CHECK LIST – CCW-5013 PEDESTRIAN DECK COATING

- CCW Representative Contact Information.**
- Installer Qualification Letter/ Verify Training**
- Verify if components of system match requirements for specified project warranty**
- Pre-Construction Meeting**
- Weather requirements – No frost, moisture present or pending and above 40 degrees**
- Substrate Inspection – See Substrate Inspection Form, ICRI CSP 2-4, 28 day cure (Note: surface prep is critical for success with deck coatings)**
- Follow CCW Plywood Deck Technical Release for plywood substrates**
- Conduct ASTM Rubber Mat Test for moisture**
- Install field mock-up and get owner to sign off on appearance**
- Saw cut and seal cracks over 1/16th inch. Detail and pre-treat all cracks with CCW-501T**
- If metal pan is used, must be vented**
- Always allow for and verify proper cure time between coats**
- CCW Product Data Sheets, MSDSs and Shop Drawings**
- Provide adequate ventilation**
- CCW Inspection Forms**
- Have Access to Project Spec and Drawings**
- CCW Products: 557 Primer, CCW-501-T Detail Coat, CCW-501 Base Coat, 503 Top Coat, CCW-201 Sealant**
- Tools & Supplies:**
  - Solvent Resistant ¾ inch nap roller**
  - Notched Squeegee (1/4 inch notch)**
  - Mil Thickness gauge**
  - Shot blast equipment**
  - Solvent for cleaning**
  - Push broom or vacuum**
  - Appropriate size clean dry rounded silica sand**
  - Duck tape**
  - Angle grinder with concrete blade**
  - Caulk gun**
  - Chalk line**
- Safety Equipment**
  - Personal Protection Devices and OSHA Approved Safety Equipment for all workers on the jobsite**
  - Fire extinguisher**
  - Protective clothing**
  - Respirator**
  - Hardhat**

