



BaseGrip™ ADHESION PROMOTER

DESCRIPTION

BaseGrip Adhesion Promoter is an additive designed to increase the adhesion of CCW-501 or Eco-Fast II Base Coat to properly prepared concrete surfaces.

TYPICAL USE

BaseGrip is mixed into CCW-501 or Eco-Fast II Base Coat immediately prior to installation. The additive allows the coating to form a high strength bond with the concrete, eliminating the need for a separate primer. Concrete surfaces must be clean, dry, free of laitance and properly prepared to receive coating in order to obtain good results.

PACKAGING

1 Pint (0.24 liter) cans, 9 per carton

INSTRUCTIONS

For use on properly prepared concrete surfaces only. Surface should be properly sloped to drain freely and eliminate the ponding of water. The surface must be clean, dry and free of dirt, oil, grease or other contamination. Laitance and the high water to cement ratio gel that comes to the surface have very low strength and adhesion to the base concrete and must be removed. Acceptable methods of cleaning are vacuum shotblasting, sandblasting, acid etching or mechanical grinding followed by the complete and thorough removal of any residue.

Pour contents of one (1) pint of BaseGrip Adhesion Promoter into one (1) five gallon pail of CCW-501 or Eco-Fast II Base Coat. Stir with a slow speed mixer for 5 minutes. See CCW Deck Coating Data sheet for complete deck coating system installation guidelines.

WARNINGS AND HAZARDS

Before use refer to MSDS for important warnings and safety information. Use only in areas with adequate ventilation. Avoid breathing vapors. Keep away from heat and flame. Avoid contact with eyes and skin. In the event of skin contact, remove immediately and wash with warm, soapy water. Wear eye protection. Always wash hands before eating. Keep container closed when not in use.

LIMITED WARRANTY

CARLISLE COATINGS & WATERPROOFING INCORPORATED (CARLISLE) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any CARLISLE materials prove to contain manufacturing defects that substantially affect their performance, CARLISLE will, at its option, replace the materials or refund its purchase price.

This limited warranty is the only warranty extended by CARLISLE with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. CARLISLE specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of CARLISLE's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the CARLISLE material in question.