



# CCW-557

## Two-Part Epoxy Primer

### DESCRIPTION

CCW-557 is a two component, epoxy-polyamide penetrating primer/sealer. CCW-557 is used to seal concrete or plywood substrates and to improve adhesion when applying one-or two-part polyurethane coatings or sealants.

Mixing instructions: CCW-557 is a two part material. Add all of the Part A to Part B and mix thoroughly. After mixing, allow mixed material to stand for 15 minutes (minimum). This time, known as induction time, is critical and must be observed. Use within 8 hours of mixing.

### APPLICATION

Apply at a rate of 300 square feet per gallon. Avoid puddling or ponding of the primer. Allow primer to dry 1 hour minimum, 8 hours maximum at 75°F prior to further coating application.

All fluid applied product application rates are based on theoretical coverage relative to the percentage of solids in the material. These are minimum application rates to achieve the required dry film thickness for the system and do not account for substrate condition or porosity. A thicker application of the product may be necessary to achieve the required dry film thickness for system relative to the substrate.

### WARNINGS AND HAZARDS

Extremely flammable liquid and vapors. Vapors may cause flash fire. Use only with adequate ventilation and avoid breathing the vapors. Avoid contact with the eyes and skin. Avoid ingestion. Workers should wear approved breathing apparatus, protective clothing and eye protection. Refer to MSDS before use for important safety information.

### LIMITED WARRANTY

Carlisle Coatings & Waterproofing, Incorporated (Carlisle) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any Carlisle materials prove to contain manufacturing defects that substantially affect their performance, Carlisle will, at its option, replace the materials or refund its purchase price.

This limited warranty is the only warranty extended by Carlisle with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. Carlisle specifically disclaims liability for any incidental, consequential or other damages, including, but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of Carlisle's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the Carlisle material in question.