



# CCW-Deck Coating Reinforcing Fabrics

## REINFORCING FABRIC DCH

### DESCRIPTION

The CCW-Reinforcing Fabric DCH is a white polyester fabric designed to work in conjunction with CCW Deck Coating Systems and Liquid Applied Membranes. The DCH fabric is for use in horizontal and detailing applications (see Deck Coating details for proper installation).

### TYPICAL PROPERTIES

Weight	3.0 oz. per square yard
Tensile Strength	45 lbs.
Elongation	21%
Widths	4, 6, 12, 40 inches
Roll Length	324 feet

## REINFORCING FABRIC DCV

### DESCRIPTION

The CCW-Reinforcing Fabric DCV is a white polyester fabric designed to work in conjunction with the CCW Liquid Applied Membrane Systems. The DCV fabric is for use in vertical applications (see Deck Coating details for proper installation).

### TYPICAL PROPERTIES

Weight	2.75 oz. per square yard
Tensile Strength	40 lbs.
Elongation	20%
Widths	40 inches
Roll Length	324 feet

### LIMITED WARRANTY

Carlisle Coatings and Waterproofing Incorporated (Carlisle) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any Carlisle materials prove to contain manufacturing defects that substantially affect their performance, Carlisle will, at its option, replace the material or refund the purchase price.

This limited warranty is the only warranty extended by Carlisle with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. Carlisle specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of Carlisle's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the Carlisle material in question.

