



DrainGrip™ -R

Drainage Composite Adhesive

DESCRIPTION

CCW DrainGrip-R is a roller grade, solvent based adhesive specially formulated to adhere protection courses and drainage composites to a variety of waterproofing membranes.

TYPICAL USES

CCW DrainGrip is formulated to provide a fast and economical installation solution for CCW MiraDRAIN drainage composites and protection courses (CCW 200V/300HV).

FEATURES / BENEFITS

- Rapid strength buildup
- Excellent resistance to aging, heat, and moisture
- Bond strength increases with age

INSTALLATION

Apply CCW DrainGrip-R adhesive 4" (10cm) wide along the perimeter of the protection board or drainage composite, using either a brush or roller. Also apply the CCW DrainGrip to the corresponding area on the waterproofing substrate. Dry time will depend on temperature, humidity, coating weight and surface conditions.

When using CCW DrainGrip on polystyrene protection boards, apply CCW DrainGrip adhesive thinly to avoid 'puddling' and possible damage to the polystyrene product.

MAINTENANCE

CCW DrainGrip requires no maintenance if installed in accordance with the manufacturer's instructions.

TECHNICAL SERVICES

Complete technical assistance is available from Carlisle Coatings & Waterproofing and its sales representatives. Services include assistance during the design, specification and installation stages.

CAUTIONS & LIMITATIONS

CCW DrainGrip contains solvents. No open flames, sparks, or smoking should be allowed in the immediate area. Dispose of in accordance with local, state, and federal EPA regulations. Vapors are harmful. Use in a well ventilated area. Avoid contact with eyes, skin, or clothing, Wash thoroughly after handling. HARMFUL OR FATAL IF SWALLOWED. Do not induce vomiting. Call a physician immediately. Refer to MSDS for other warnings and safety information.

LIMITED WARRANTY

Carlisle Coatings and Waterproofing Incorporated (Carlisle) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any Carlisle materials prove to contain manufacturing defects that substantially affect their performance, Carlisle will, at its option, replace the material or refund the purchase price.

This limited warranty is the only warranty extended by Carlisle with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. Carlisle specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of Carlisle's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the Carlisle material in question.

TECHNICAL DATA

PROPERTY	RESULTS
Coverage	1 gallon will apply approximately 400ft ² (37m ²) of drainage composite or protection course
Storage Life	1 year if kept sealed and stored properly
Expiration Date	1 year from the 7 digit lot number (Lot # = yymmdd#, the last number is for internal use)
Packaging	(4) 1 gallon (3.78 liter) containers; 5 gallon (18.93 liters) containers
VOC	594 g/l

